

# 8002 Series

## LED Surface Mount

Type:

Catalog Number:

Project/Location:

Approved By:



### SPECIFICATIONS

**Housing:** Heavy-duty construction of corrosion resistant aluminum. Stainless steel hardware.

**Gasket:** Closed cell silicone foam gasket. Seals out moisture, dust, and insects for weather-tight operation.

**Mounting:** Surface over standard J-box.

**Lens:** Matte white acrylic lens diffuser.

**Driver:** Constant current and Universal input voltage 120-277V, 50-60Hz line voltage frequency. Operating temperature -20°C to 40°C, Power Factor  $\geq .90$ .

**LED:** Specify amber (A), blue (B), green (G), red (R), or 3000 (30K), 3500 (35K), 4000 (40K), and 5000 (50K) – 40K standard.

**Lumens:** 1000.

**Finish/Colors:** Zinc based primer with polyester powder coat finish in Matte Black (MB), Matte White (MW), Matte Bronze (BZ), Silver Gray (SG), or a custom color (CC).

**Testing:** LM79, LM80, ETL.  
Conforms to UL Standard 1598. Suitable for wet locations.

*See options page for additional information or consult factory.*



EMERGENCY BATTERY  
BACKUP AVAILABLE

Series	Source	Wattage/Max
8002	LED	10W


### ORDERING EXAMPLE

8002 – 10LED – 40K – UNV – MB

TOP VIEW



SIDE VIEW



## ELCAST LIGHTING

815 S. Kay Ave., Addison, IL 60101 USA • 630.543.5390  
www.ElcastLtg.com • ElcastLtg@ElcastLtg.com

**Made in USA** – 5 year limited warranty

©2017. Specifications are subject to change without notice. Consult factory for verification.

REV 03-19